Highly efficient and precise processing inside transparent materials

Kazuyuki HIRAO



Processing using femtosecond laser Inside transparent materials



Refractive index distribution can be created inside various transparent materials with a spatial resolution of less than micrometer by focusing femtosecond laser pulses.

Optical waveguides, 3D optical data storage, space selective light emission, coloration and ion migration inside glasses.



Highly efficient laser processing with an LCOS-SLM



Ultrafast microscopic photograph of laser processing inside various transparent materials



Material deformation process after irradiation with a focused laser pulse can be observed with a time resolution of 10⁻¹³ second. With this technique, we can elucidate the origin of damage after loading external force to various solid materials.

Nanostructuring inside a glass - Nanograting





Rewritable 5D (= X + Y + Z + E + δ) optical storage with a capacity of 37 GB/cm³ corresponding to about 10 times lager than that of *Blue-ray* disc.



Multiple light spots can be generated by modulating the phase distribution of a laser pulse.



Application

3D structure



Micro optics



Copyright © 2011 KYOTO UNIVERSITY All Rights Reserved.

Graduate School of Engineering Kyoto-daigaku-Katsura, Nishikyo-ku, Voto 615-8510, Japan Phone: 81-75-383-2409 FAX: 81-75-383-2410 E-mail: hirao@bisco1.kuic.kyoto-u.ac.jp